



1. HOUSING MATERIAL	: PBT, UL94V-0.
2. CONTACT MATERIAL	: PHOSPHOR BRONZE Ø0.46mm.
3. CONTACT PLATING	: GOLD PLATING OVER NICKEL, SEE TABLE.
4. MATING/UNMATING FORCE:	: 30N Max.
5. RETENTION STRENGTH	: 50N for 60s±5s.
6. DURABILITY	: 750 CYCLES MIN.

D

第一视角

版本	05
----	----



1. 储存温度: $-40^{\circ}\text{C}\sim 85^{\circ}\text{C}$ 相对湿度 $<80\%$.
2. 工作温度: $-40^{\circ}\text{C}\sim 85^{\circ}\text{C}$
3. 储存时间: 12个月

1802984C083	RJ45 1X4 5224-S W/O SHIELD 8P4C//5224四路插座整体式 8P4C(1236位)6u" (圆针)带CZT	PBT BLACK 黑
1802984A096	RJ45 1X4 5224-S W/O SHIELD 8P4C//5224四路插座整体式 8P4C(1236位) 6/F(圆针)带CZT	PBT BLACK 黑
10202984C001	RJ45 1X4 5224-S W/O SHIELD 8P4C//5224四路插座整体式 8P4C(1.2,3.6位)6u" (圆针)	PBT YELLOW黄D0C420013
10202988A008	RJ45 1X4 5224-S W/O SHIELD 8P8C//5224四路插座整体式 8P8C 6u" (圆针)带CZT	PBT YELLOW 114C(D4016) 黄
10202988F005	RJ45 1X4 5224-S W/O SHIELD 8P8C//5224四路插座整体式 8P8C 30u" (圆针)带CZT	PBT YELLOW(D0C420013) 黄
10202988G002	RJ45 1X4 5224-S W/O SHIELD 8P8C//5224四路插座整体式 8P8C 50u" (圆针)带CZT	PBT YELLOW(D0C420013) 黄
10202988C096	RJ45 1X4 5224-S W/O SHIELD 8P8C//5224四路插座整体式 8P8C 6u" (圆针)带CZT	PBT YELLOW(D0C420013) 黄
10202988A007	RJ45 1X4 5224-S W/O SHIELD 8P8C//5224四路插座整体式 8P8C 6/F(圆针)带CZT	PBT YELLOW(D0C420013) 黄
10202988A096	RJ45 1X4 5224-S W/O SHIELD 8P8C//5224四路插座整体式 8P8C 6/F(圆针)	PBT BLACK 黑
P/N	DESCRIPTION	MATERIAL COLOR