

Technical drawing of a mechanical part, likely a nozzle or probe, showing dimensions in millimeters. The drawing includes a side view and a cross-sectional view. Key dimensions include:

- Overall width: 18.30
- Top width: 14.30
- Top width to centerline: 11.36
- Top thickness: 3.00
- Side thickness: 1.50
- Main body height: 12.00
- Nozzle tip diameter: 1.80
- Nozzle base diameter: 6.90
- Nozzle base to centerline: 9.60
- Nozzle base to outer edge: 2.30
- Tolerance on the right side: 3.5 ± 0.3

1. 额定电压: 125 VAC RMS
2. 额定电流: 1.5 AMP
3. 接触电阻: 20mΩ MAX.
4. 绝缘电阻: 1000Ω MIN. @500 VDC
5. 耐压强度: 1000 V AC 或 1500V DC RMS @
0.5mA 50 Hz 或 60 Hz 一分钟

1. VOLTAGE RATING	: 125 VAC RMS.
2. CURRENT RATING	: 1.5 AMP.
3. CONTACT RESISTANCE	: 20 MILLIOHMS MAX.
4. INSULATION RESISTANCE	: 1000 MEGOHMS MIN @ 500 VDC
5. DIELECTRIC STRENGTH	: 1000 V AC OR 1500V DC RMS @ 0.5mA 50 Hz / 60 Hz 1 Minute
<u>MECHANICAL:</u>	
1. HOUSING&INSERT& MATERIAL	: SEE TABLE UL94V-0.
2. CONTACT MATERIAL	: PHOSPHOR BRONZE Ø0.46mm.
3. PLATING	: GOLD PLATING OVER NICKEL.
4. OPERATING LIFE	: 750 CYCLES MIN.
5. MATING/UNMATING FORCE:	: 30N Max.
6. RETENTION STRENGTH:	: 50N FOR 60S±5S.

1. STORAGE : -40°C TO +85°C RELATIVE HUMIDITY<80%.
2. OPERATION : -40°C TO +85°C.

	PART NUMBER	PART NUMBER(OLD)	DESCRIPTION	CONTACT	PALTING	HOUSING&INSERT	MATERIAL
2		B703N-441S-M003	SE-616PCB 4P4C PCB JACK	15u"		PBT	BLACK
3		B703N-441S-M004	SE-616PCB 4P4C PCB JACK	15u"		PBT	WHITE
4		B703N-4403-U004	SE-616PCB 4P4C PCB JACK	3u"		PA66	WHITE
5		B703N-4406-M003	SE-616PCB 4P4C PCB JACK	6u"		PBT	GREY
6		B703N-44GF-M004	SE-616PCB 4P4C PCB JACK	G/F		PBT	WHITE
6		B703N-44GF-M006	SE-616PCB 4P4C PCB JACK	G/F		PBT	BLACK
6	10246244C001	B703N-4406-M002	SE-616PCB 4P4C PCB JACK	6u"		PBT	BLACK
6		B703N-4450-M004	SE-616PCB 4P4C PCB JACK	50"		PBT	WHITE
6		B703N-4403-M003	SE-616PCB 4P4C PCB JACK	3u"		PBT	GREY
7		B703N-44GF-M003	SE-616PCB 4P4C PCB JACK	G/F		PBT	GREY
8		B703N-4403-M006	SE-616PCB 4P4C PCB JACK	3u"		PBT	BLACK
	10246244C002	B703N-4406-M004	SE-616PCB 4P4C PCB JACK	6u"		PBT	WHITE

CZT[®] 温州意华接插件股份有限公司
WENZHOU YIHUA CONNECTOR CO., LTD

SE-616PCB 4P4C PCB JACK

.0	± 0.25
.00	± 0.20
.000	± 0.10
ANGLES	± 0.5°

REV.	版本
08	