

CZT

SPECIFICATION FOR APPROVAL

CUSTOMER _____

CUSTOMER'S PART NO. _____ REV. _____

DESCRIPTION RJ45+USB ICM(1000Base-T 1Port)

CZT'S PART NO. JBGU10830016 REV. C

ISSUE NO. _____

ISSUE DATE JAN.16,2019

☐ APPROVED

☐ REJECTED:

☐ APPROVED UNDER
THE CONDITIONS:

SuZhou Yihua Communicated Connector Co., Ltd.

Add: No.1558, Linhu East Road, Foho New&Hi-tech industrial Development Zone,
Wujiang,Jiangsu,P.R.C.

TEL:+86-512-82078810

FAX:+86-512-82078858

DongGuan Yizhao Electronic Co., Ltd.

Add: Yihua Holdings Industrial park, Cuntou district, Hu'men Town,
Dongguan,Guangdong,P.R.C.

TEL:+86-769-8624 0111

FAX:+86-769-8624 0238







Note:

1. This specification is the proprietary of Yihua Communicated Connector Co., Ltd. and is not allowed to be revealed to third party without any written approval.
2. This specification is valid within 1 year before approval, and for any updated specification information required, please contact with CZT's sales window before order releases.

CZT

SPECIFICATION FOR APPROVAL

2. Revision Change Record

Customer Part No.: CZT Part No.: JBGU10830016 Part Name: RJ45+USB ICM(1000Base-T 1Port)					Rev.: C
					
Rev	Description	Drawn	Designed	Approved	Issue Date
A	Specification issued		SunWenqun	Topup.Liu	OCT.15 2011
B	Change From: 5-1. Label: Plug In Side  To: Label 5-1. Label: Plug In Side 	ChenLingjuan	SunWenqun	Topup.Liu	DEC.21 2012
C	Change From: 5-3. Keep-Out Area (Component Side View): Connector Boundary  To: 5-3. Keep-Out Area (Component Side View): Connector Boundary 	ChenLingjuan	SunWenqun	Topup.Liu	JUN.28 2013

CZT

SPECIFICATION FOR APPROVAL




Customer Part No.:
CZT Part No.: JBGU10830016
Part Name: RJ45+USB ICM(1000Base-T 1Port)

Rev.: C



4. Mechanical Dimension and Notes:

4-1. Mechanical Dimension:



UNIT : mm / inch

A = 16.89 / 0.665

B = 21.08 / 0.830

C = 25.78 / 1.015

D = 3.45 / 0.136

Unless otherwise specified, all dimensions tolerances is ± 0.254 / 0.010.

4-2. Notes:

- CONNECTOR MATERIAL:
HOUSING: THERMOPLASTIC BLACK UL94 V-0
SHIELD: Brass
SHIELD PLATING: NICKEL
CONTACT: PHOSPHOR BRONZE
CONTACT PLATING: SELECTIVE GOLD, 6 MICRO-INCHES MIN IN CONTACT AREA
- PIN NOT ELECTRICALLY CONNECTED MAYBE OMITTED SEE ELECTRICAL DRAWING FOR OMITTED PINS
- RJ45 CAVITIES CONFORM TO FCC RULES AND REGULATION PART 68.
- THE PART IS RECOMMENDED FOR WAVE SOLDERING PROCESS PEAK SOLDERING TEMPERATURE IS 260°C MAX, 10 SECS MAX
- OPERATING TEMPERATURE $T = 0^{\circ}\text{C}$ TO $+70^{\circ}\text{C}$.
- STORAGE TEMPERATURE $T = -40^{\circ}\text{C}$ TO $+85^{\circ}\text{C}$.

LED SPECIFICATION				
STANDARD LED	WAVELENGTH	Forward Current	Forward V(max)	TYP
GREEN	565nm	20 mA	2.4V	2.2V
YELLOW	590nm	20 mA	2.5V	2.1V

Drawn by

Designed by

SunWenqun

Approved by

Topup.Liu

CZT

SPECIFICATION FOR APPROVAL


Customer Part No.:
CZT Part No.: JBGU10830016
Part Name: RJ45+USB ICM(1000Base-T 1Port)

Rev.: C




5. Label and Recommended PWB Layout and Suggested Panel Opening:
5-1. Label:

Plug In Side



- 5-2. Suggested Panel Opening:



UNIT: mm / inch
Tolerances: ± 0.10 / 0.004

REFERENCE ONLY

CZT


SPECIFICATION FOR APPROVAL

Customer Part No.:
CZT Part No.: JBGU10830016
Part Name: RJ45+USB ICM(1000Base-T 1Port)

Rev.: C




5-3. Keep-Out Area (Component Side View):



UNIT: mm / inch
Tolerances: ± 0.10 / 0.004

Plug-in side

5-4. Recommended PWB Layout (Component Side View):




UNIT: mm / inch
Tolerances: ± 0.10 / 0.004

Plug-in side

CZT


SPECIFICATION FOR APPROVAL

1. Cover Page

Customer Part No.: CZT Part No.: JBGU10830016 Part Name: RJ45+USB ICM(1000Base-T 1Port)	Rev.: C
	

6. Circuit Schematic and Electronical Specifications:

6-1. Circuit Schematic:



6-2. Electronical Specifications:

- 1.0 Turn Ratio @100KHz: (P11~P10):(J1~J2) = 1:1±5%
(P4~P5):(J3~J6) = 1:1±5%
(P3~P2):(J4~J5) = 1:1±5%
(P8~P9):(J7~J8) = 1:1±5%
- 2.0 Primary Inductance: 350uH MIN @100KHZ,0.1V 8mA DC BIAS
- 3.0 DC Resistance: 1.2 OHMS MAX
- 4.0 Insertion Loss: 1-100MHz -1.0dB MAX
100-125MHz -1.2dB MAX
- 5.0 Return Loss: 1-40MHz -16dB MIN
40-60MHz -12dB MIN
60-80MHz -10dB MIN
80-100MHz -8dB MIN
- 6.0 CROSS TALK: 1-100MHz -30dB MIN
- 7.0 COMMON TO COMMON MODE ATTENUATION: 1-100MHz -30dB MIN
- 8.0 Isolation: PHY Side to Line Side: 2250VDC