

CZT

SPECIFICATION FOR APPROVAL

CUSTOMER _____

CUSTOMER'S PART NO. _____ REV. _____

DESCRIPTION RJ45 ICM(1000Base-T 4Port)

CZT'S PART NO. JDD221320039 REV. A

ISSUE NO. _____

ISSUE DATE NOV.18,2015

☐ APPROVED

☐ REJECTED:

☐ APPROVED UNDER
THE CONDITIONS:

SuZhou Yihua Communicated Connector Co., Ltd.

Add: No.1558, Linhu East Road, Foho New&Hi-tech industrial Development Zone,
Wujiang,Jiangsu,P.R.C.

TEL:+86-512-82078810

FAX:+86-512-82078858

DongGuan Yizhao Electronic Co., Ltd.

Add: Yihua Holdings Industrial park, Cuntou district, Hu'men Town,
Dongguan,Guangdong,P.R.C.

TEL:+86-769-8624 0111

FAX:+86-769-8624 0238


Note:

1. This specification is the proprietary of Yihua Communicated Connector Co., Ltd. and is not allowed to be revealed to third party without any written approval.
2. This specification is valid within 1 year before approval, and for any updated specification information required, please contact with CZT's sales window before order releases.

CZT

SPECIFICATION FOR APPROVAL

2. Revision Change Record

Customer Part No.: CZT Part No.: JDD221320039 Part Name: RJ45 ICM(1000Base-T 4Port)					Rev.: A
					
Rev	Description	Drawn	Designed	Approved	Issue Date
A	Specification issued	ChenLingjuan	PangZhengyang	Topup.Liu	NOV.18 2015
					

CZT




SPECIFICATION FOR APPROVAL

Customer Part No.:
CZT Part No.: JDD221320039
Part Name: RJ45 ICM(1000Base-T 4Port)

Rev.: A



4. Mechanical Dimension and Notes: 4-1. Mechanical Dimension:



UNIT : mm / inch

A = 31.20 / 0.1228

B = 25.53 / 1.005

C = 41.53 / 1.635 MAX

D = 2.59 / 0.102

Unless otherwise specified, all dimensions
tolerances is ± 0.254 / 0.010.

4-2. Notes:

- CONNECTOR MATERIAL:
HOUSING: THERMOPLASTIC BLACK UL94 V-0
SHIELD: Brass
SHIELD PLATING: NICKEL
CONTACT: PHOSPHOR BRONZE
CONTACT PLATING: GOLD, 6 MICRO-INCHES MIN IN CONTACT AREA
- PIN NOT ELECTRICALLY CONNECTED MAYBE OMITTED SEE ELECTRICAL DRAWING FOR OMITTED PINS
- RJ45 CAVITIES CONFORM TO FCC RULES AND REGULATION PART 68.
- THE PART IS RECOMMENDED FOR WAVE SOLDERING PROCESS PEAK SOLDERING TEMPERATURE IS 260°C MAX, 10 SECS MAX
- OPERATING TEMPERATURE $T = -40^{\circ}\text{C}$ TO $+85^{\circ}\text{C}$.
- STORAGE TEMPERATURE $T = -40^{\circ}\text{C}$ TO $+85^{\circ}\text{C}$.

LED SPECIFICATION				
STANDARDLED	WAVELENGTH	Forward Current	Forward V(max)	TYP
GREEN	565nm	20 mA	2.4V	2.2V
YELLOW	590nm	20 mA	2.5V	2.1V

Drawn by

ChenLingjuan

Designed by

PangZhengyang

Approved by

Topup.Liu

CZT

SPECIFICATION FOR APPROVAL


Customer Part No.:
CZT Part No.: JDD221320039
Part Name: RJ45 ICM(1000Base-T 4Port)

Rev.: A




5. Label and Recommended PWB Layout and Suggested Panel Opening:
5-1. Label:

Plug In Side



- 5-2. Suggested Panel Opening:



UNIT: mm / inch
Tolerances: ± 0.10 / 0.004

REFERENCE ONLY

CZT


SPECIFICATION FOR APPROVAL

Customer Part No.:
CZT Part No.: JDD221320039
Part Name: RJ45 ICM(1000Base-T 4Port)

Rev.: A



5-3. Keep-Out Area (Component Side View):




Plug-in side

UNIT: mm / inch

Tolerances: ± 0.10 / 0.004

5-4. Recommended PWB Layout (Component Side View):



UNIT: mm / inch

Tolerances: ± 0.10 / 0.004

CZT

SPECIFICATION FOR APPROVAL


Customer Part No.:
CZT Part No.: JDD221320039
Part Name: RJ45 ICM(1000Base-T 4Port)

Rev.: A



6. Circuit Schematic and Electronical Specifications:

6-1. Circuit Schematic:



6-2. Electronical Specifications:

- 1.0 Turn Ratio @100KHz: (P2~P1):(J1~J2) = 1:1±5%
(P4~P3):(J3~J6) = 1:1±5%
(P6~P5):(J4~J5) = 1:1±5%
(P8~P7):(J7~J8) = 1:1±5%
- 2.0 Primary Inductance: 350uH MIN @ 100KHz,0.1V,8mA
120uH MIN @ 100KHz,0.1V,19mA
- 3.0 DC Resistance: 1.2 OHMS MAX
- 4.0 Insertion Loss: 1-100MHz -1.0dB MAX
100-125MHz -1.2dB MAX
- 5.0 Return Loss: 1-40MHz -16dB MIN
40-60MHz -12dB MIN
60-80MHz -10dB MIN
80-100MHz -8dB MIN
- 6.0 Cross Talk: 1-100MHz -30dB MIN
- 7.0 COMMON TO COMMON MODE ATTENUATION: 1-100MHz -30dB MIN
- 8.0 Isolation: PHY Side to Line Side: 2250VDC
- 9.0 DC CURRENT/VOLTAGE RATING-PSE PINS: 720mA @57V(CONTINUOUS)